


ref	930541
name	POWERLED CONVERTER 8W 350mA 230V IP20



Mains voltage: 220-240 V \pm 10%
Mains frequency: 0 Hz, 50-60 Hz
Electronic short-circuit protection
Overload protection
Protection against "no load" operation
Degree of protection: IP20

Protection class II

SELV equivalent
Power factor: 0.6
Screw terminals: 2.5 mm²
Quantity of screw terminals:
 1x2-poles primary
 1x2-poles secondary

Service life time: 50,000 hrs
permanent operation when maximum
temperature t_{cmax} . at t_c point will not
be exceeded;
failure rate: < 0.2% per 1000 hrs



**designed for DC-operation (mains frequency: 0 Hz)
and can be used for emergency power supplies.**

Max. output W	Mains voltage 0 Hz, 50-60 Hz V	Mains current mA	Current output DC mA	Voltage output DC V	Max. voltage without load DC V	Ambient temperature t_a °C	Casing temperature t_c °C	Drawing	Weight g
------------------	---	---------------------	----------------------------	---------------------------	--------------------------------------	------------------------------------	-----------------------------------	---------	-------------

Dimensions: 65 x 30.7 x 21.5 mm

8	176/264 220/240	60/40 91/88	350 \pm 5%	2-24	25	-20 to 50	80	A	33
---	--------------------	----------------	--------------	------	----	-----------	----	---	----



**ALWAYS DISCONNECT MAINS POWER SUPPLY
FROM CONVERTER BEFORE SWITCHING "ON"
LED LUMINAIRES TO PREVENT HOT PLUGGING ISSUES**