


OBO/UBO QR-C51 WT

floorspots



OBO ROUND QR-C51 WT




QR-C51 Alu Refl 50W
GX5,3
12V - 50Hz
dimnable
↻ 355° 30°
INTERIOR USE MAX. 35W



	Clear Glass	Matt Glass
STAINLESS STEEL	365110	365115
ANODISED ALU	366110	366115

- FLOORTUBE 366118 p.248
- FLOORBOX 366119 p.248

OBO SQUARE QR-C51 WT




QR-C51 Alu Refl 50W
GX5,3
12V - 50Hz
dimnable
↻ 355° 30°
INTERIOR USE MAX. 35W



	Clear Glass	Matt Glass
STAINLESS STEEL	365210	365215
ANODISED ALU	366210	366215

- FLOORTUBE 366118 p.248
- FLOORBOX 366119 p.248

UBO ROUND QR-C51 WT




QR-C51 Alu Refl 50W
GX5,3
12V - 50Hz
dimnable
↻ 355° 30°
INTERIOR USE MAX. 35W



	Clear Glass	Matt Glass
STAINLESS STEEL	365100	365105
ANODISED ALU	366100	366105

- FLOORTUBE 366108 p.248
- FLOORBOX 366109 p.248

UBO SQUARE QR-C51 WT



QR-C51 Alu Refl 50W
GX5,3
12V - 50Hz
dimnable
↻ 355° 30°
INTERIOR USE MAX. 35W



	Clear Glass	Matt Glass
STAINLESS STEEL	365200	366205
ANODISED ALU	366200	365205

- FLOORTUBE 366208 p.248
- FLOORBOX 366209 p.248



	MATERIAL	TREATMENT
STAINLESS STEEL	MARINE GRADE 316	Electrolytically Polished
ANODISED ALU	AlMgSi 0,5	Technical Anodised

